

WE CARE

SLUDGE DECANTER WC SDC

The sludge decanter WC SDC type is suitable for the clarification of water coming from civil or industrial activities

Allows a continuous waste water treatment .

The sludge generated in the treatment process can be filtered and collected in a WC PSS unit.

Advantages

- Absence of mechanical parts in motion
- Immune to corrosive liquids action
- No energy consumption
- Easy and simple installation
- Low cost
- Low maintenance

Construction

Polypropylene
Standard colour: beige
In/out/overflow: by loose flanges



Model	Volume (m ³)	Decanting surface (m ²)	Ø In	Ø Out	Dimensions (mm)
WC SDC 50	0,50	0,50	1 ½"	1 ½"	Ø800 x H 1500
WC SDC 75	0,75	0,78	1½"	1½"	Ø1000 x H 1500
WC SDC 100	1,00	0,78	1½"	1½"	Ø1000 x H 1750
WC SDC 200	2,00	1,20	2"	2"	Ø1250 x H 1750
WC SDC 300	3,00	1,76	2"	2"	Ø1500 x H 2200
WC SDC 500	5,00	2,54	2½"	2½"	Ø1800 x H 2250
WC SDC 750	7,50	3,14	2½"	2½"	Ø2000 x H 2500
WC SDC 1000	10,00	4,90	2½"	2½"	Ø2500 x H 3350
WC SDC 2000	20,00	9,60	3"	3"	Ø3500 x H 3350

WWW.ventilaqua.com

WECARE International Dealer

